



## Suitability for agricultural irrigation of Mampostón sub-basin surface water, Mayabeque, Cuba

### Aptitud para el riego agrícola del agua superficial de la subcuenca Mampostón, Mayabeque, Cuba

 Lilisbet Guerrero-Domínguez<sup>1\*</sup>,  María Aurora Mesa-Pérez<sup>2</sup>,  Daylén Hernández-Rodríguez<sup>2</sup>,  
 Oscar Díaz-Rizo<sup>3</sup>,  José Miguel Sánchez-Pérez<sup>4</sup>

<sup>1</sup>Instituto Nacional de Ciencias Agrícolas (INCA), carretera San José-Tapaste, km 3½, Gaveta Postal 1, San José de las Lajas, Mayabeque, Cuba. CP 32 700.

<sup>2</sup>Universidad Agraria de La Habana “Fructuoso Rodríguez Pérez”, carretera a Tapaste y Autopista Nacional, San José de las Lajas, Mayabeque, Cuba.

<sup>3</sup>Instituto Superior de Tecnología y Ciencias Aplicadas (InSTEC), Universidad de La Habana, La Habana, Cuba.

<sup>4</sup>Laboratoire de Écologie Fonctionnelle et Environnement de Toulouse (EcoLab), France, CNRS.

**ABSTRACT:** It is common to find effects on agricultural production derived from water quality, so the evaluation of its aptitude for irrigation is decisive to ensure food safety. The present work aimed to evaluate the chemical-physical and microbiological quality of the surface water of Mampostón sub-basin, for its use in agricultural irrigation. The parameters pH, electrical conductivity (EC), majority anions and cations, heavy metals (HM), dissolved organic carbon (DOC) and particular (POC), chemical (COD) and biological oxygen (BOD<sub>5</sub>) demand and content of total and fecal coliforms. The spatio-temporal variability of these parameters was determined by bifactorial ANOVA, establishing that the differences were in the main effects (monitoring stations and sampling time) and not in the interaction between them. The analysis of spatial variability indicated that stations G2, G3 (Ganuzá river) and M5 (Mampostón river), presented organic and soluble salts contributions that establish limitations for their use. The average concentrations of dissolved Pb exceeded the permissible limits in stations G1, G2, G4 (Ganuzá river), M2, M3 (Mampostón river) and P1 (Pedroso diverter dam), which disables their exploitation. The content of fecal coliforms compromises the quality of the water in station M5 (Mampostón river). The water from the rest of the sampling stations in the Pedroso diverter dam and the Mampostón dam are suitable for use in agricultural irrigation. A monitoring program and management strategy should be designed in the area.

**Key words:** irrigation, heavy metals.

**RESUMEN:** Es común encontrar afectaciones en la producción agrícola derivadas de la calidad de las aguas, por lo que la evaluación de su aptitud para el riego es determinante para asegurar la inocuidad de los alimentos. El presente trabajo tuvo como objetivo evaluar la calidad químico-física y microbiológica del agua superficial de la subcuenca Mampostón, para su uso en el riego agrícola. Se determinaron los parámetros pH, conductividad eléctrica (CE), aniones y cationes mayoritarios, metales pesados (MP), carbono orgánico disuelto (COD) y particular (COP), demanda química (DQO) y biológica de oxígeno (DBO<sub>5</sub>) y contenido de coliformes totales y fecales. La variabilidad espacio-temporal de estos parámetros se determinó mediante ANOVA bifactorial, es decir, se estableció que las diferencias radicaron en los efectos principales (estaciones de monitoreo y época de muestreo) y no en la interacción entre los mismos. El análisis de la variabilidad espacial indicó que las estaciones G2, G3 (río Ganuzá) y M5 (río Mampostón), presentaron aportes orgánicos y de sales solubles que establecen limitaciones para su uso. Las concentraciones medias de Pb disuelto superaron los límites permisibles en las estaciones G1, G2, G4 (río Ganuzá), M2, M3 (río Mampostón) y P1 (derivadora Pedroso), lo que inhabilita su explotación. El contenido de coliformes fecales compromete la calidad del agua en la estación M5 (río Mampostón). El agua del resto de las estaciones de muestreo en la derivadora Pedroso y la presa Mampostón son aptas para su uso en el riego agrícola. Debe diseñarse un programa de monitoreo y una estrategia de manejo en el área.

**Palabras clave:** riego, metales pesados.

\*Author for correspondence: [liligd@inca.edu.cu](mailto:liligd@inca.edu.cu)

Received: 13/06/2019

Accepted: 17/03/2021

This is an open access article distributed under the terms of the Creative Commons Attribution-NonCommercial (BY-NC 4.0). <https://creativecommons.org/licenses/by-nc/4.0/>



## INTRODUCTION

Water quality for irrigation is determined by the quantity and type of salts that constitute it, being the main parameters established to measure the agricultural suitability of a water, the sodium adsorption ratio (SAR) and the electrical conductivity (EC). This is because the most important risk related to irrigation is creating saline soils (1).

However, irrigation water quality, if it comes from places close to polluting sources, should not be determined only taking into account the aforementioned parameters. Increasingly, chemical pollutants (either organic or inorganic) arrive in waters, both surface and underground, which are made available to plants and which can cause their accumulation in them, with the consequent magnification along trophic chains (2). Man, as the last link in most food chains, is involved in this cycle, observing immunological, embryological, neurological and systemic affectations (3). Biological pollutants that, like chemicals, can affect the food chain, causing serious diseases, can also affect these waters. These pollutants can be: helminths, protozoa, bacteria and viruses (4).

In Cuba, the monitoring of the quality of surface and groundwater is carried out from the water quality network (RedCal), belonging to the Institute of Hydraulic Resources, using as an instrument for the integration of analytical results the Quality Index of Surface Waters (ICAsup). Among the indicators that compose it are pH (acidity or basicity), electrical conductivity (EC: content of soluble salts), dissolved oxygen (ODSAT: state of the water body with respect to its dissolved oxygen content), chemical demand of oxygen by the dichromate method (COD: organic matter present) and fecal coliforms (density of fecal bacteria) (5). Other countries have their own index taking into account the content of  $N-NH_4$ ,  $N-NO_3$  and  $PO_4$  (6,7).


From the regulatory point of view, Cuba has standards for determining drinking water quality (8) and regulates discharges to bodies of terrestrial water and sewerage (9). However, the evaluation of inorganic metallic pollutants is not carried out on a scheduled and widespread basis in the country, but rather at the level of research projects that finance studies in a specific area of interest.

The Mampostón sub-basin, object of this study, covers an area of 157.8 km<sup>2</sup>. It is strongly anthropized, as it receives direct dumping from seven industries, numerous agricultural farms, towns and highways. Surface water is used from the agricultural point of view for the irrigation of vegetables (1 026.63 ha) and in the cultivation of rice (*Oryza sativa* L.), with an area of 67.60 ha, according to data from the Ministry of Agriculture (10). There is also a large area cultivated with pastures and forest crops that do not receive direct irrigation (11). Therefore, the objective of this work was to evaluate the chemical- physical and microbiological quality of the surface water of the Mampostón sub-basin for its use in agricultural irrigation.

## MATERIALS AND METHODS

### Description of the study area

The Mampostón sub-basin is of karstic origin and its extension covers the territories included to the north by Mampostón dam, to the east by the Pedroso diverter dam, to the west by the Cueto-Ganuzza hills and to the south by the Güines hills (Figure 1).



**Figure 1.** Geographic location of the Mampostón sub-basin and sampling stations.

The samplings were carried out upstream and downstream of the seven direct pollutant sources reported by the National Institute of Hydraulic Resources (Table 1) (11). It has 100 m of separation between them for a total of 16 sampling stations: four on the Ganuzza tributary (G1-G4), five in the Mampostón tributary (M1-M5), three in the Pedroso diverter dam (P1-P3), one in the water outlet towards Güines (P4) and three in Mampostón dam (PM1- PM3). The samplings were carried out at the end of two seasons of the year differentiated by the climate in Cuba (rainy season and little-rainy season).

### Evaluation of chemical-physical parameters

In 16 sampling stations, water samples were collected in inert plastic containers with a capacity of five liters. The samples were taken manually one meter from the surface, always in the middle of the river. In the reservoirs, a rowing boat was used for the collection.

The preparation of the samples for the analysis was carried out in Cuba (chemistry laboratories of the Agrarian University of Havana) and in France (Ecolab laboratories, Toulouse). The filtration for the determinations of heavy metals (PM) was carried out according to the methodology of Casanueva *et al.* (12). The samples for organic determinations (DOC and multi-element analysis) were filtered with a 70- $\mu$ m GMA glass fiber filter previously washed with 1N HCl.

### pH and EC

Both indicators were measured in the chemistry laboratories of the UNAH, by the potentiometric method using a PHSJ-3F model pH meter with a sensitivity of 0.001.

**Table 1.** Companies related to the pollutant load of the site under study.

Polluting focus	Sampling stations	Coordinates	Residual	Category
Milk pasteurisation unit "Aljibe"	G1-G2	N 22° 55' 47.59" O 82° 7' 4.02"	Organic: Dairy Waste	III
Rum Factory "San José"	G2-G3	N 22° 55' 48.8" O 82° 6' 58.06"	Organic: stillage among others	V
Paint Factory "Raúl Cepero Bonilla"	G3-G4	N 22° 55' 40.77" O 82° 5' 45.5"	Inorganic: complex chemicals	I
CEPAM	before M1	N 22° 56' 14.71" O 82° 5' 26.77"	Organic: waste from the fry rearing process	III
Aluminum Factory	M1-M2	N 22° 56' 27.11" O 82° 4' 39.45"	Inorganic: solid waste	V
Asphalt Plant	M2-M3	N 22° 55' 49.95" O 82° 5' 0.20"	Inorganic and organic: solid and gaseous waste	V
Institute of Animal Science	M4-M5	N 22° 54' 8.44" O 82° 2' 19.18"	Organic: Seedlings and animal husbandry waste	III

### Majority anions

The anions ( $\text{Cl}^-$ ,  $\text{NO}_3^-$ ,  $\text{SO}_4^{2-}$ ,  $\text{HCO}_3^-$ ) were determined, in the chemistry laboratories of the UNAH, using volumetric procedures established by RedCal in its monitoring of water quality (13).

### Organic composition of the dissolved and particulate phases transported in suspension

Both parameters were determined in the EcoLab laboratories (Toulouse, France). The catalytic oxidation was carried out at 680 °C in a TOC-5000 Shimadzu equipment. The resulting  $\text{CO}_2$  was quantified by infrared detection and comparison with a standard curve at 0, 2, 5 and 10 ppm of potassium dipthalate (14). The reading was carried out on a ThermoFisher NA 2100 Protein equipment by combustion at 1800 °C and subsequent separation of the gas mixture by gas chromatography. For quantification, results were compared with a standard curve of aspartic acid with 36.09 % C, 5.30 % H, 12.52 % N and 0 % S.

From the results of the particular phase (POC and NOP) the C/N ratio was estimated in order to establish the origin of the organic matter.

### BOD<sub>5</sub> and COD

Both parameters were determined, using procedures established by RedCal in its monitoring of water quality (13). From their results, the BOD<sub>5</sub>/COD ratio was calculated in order to determine the degradability of the organic matter present (15).

### Composition of majority cations and heavy metals in the dissolved phase

Both procedures were carried out in the EcoLab laboratories (Toulouse, France). No concentration treatment was performed, the measurement was performed directly using ICPMS equipment. For the validation of the results, the internationally certified reference material SLRS-5 (16) was used, which is an external indicator of the quality of handling.

In the ICPMS determinations, each sample was doped with a known concentration of  $^{115}\text{In}/^{187}\text{Re}$  ( $2.032 \mu\text{g L}^{-1}$ ) as an internal standard, in order to correct any deviation in the analysis, following the formulas:

$$\delta\text{In/Re} = \frac{C(\text{In})_{\text{samplex}}}{C(\text{Re})_{\text{samplex}}} \times 100$$

$$C_{\text{rectified}} = C_{\text{measured}} \cdot \frac{\delta\text{In}}{\text{Re}}$$

where:

$\delta\text{In/Re}$ : identifies the relationship between doped concentration

equipment reading  $C(\text{In})$ : represents In concentration

$C(\text{Re})$ : represents Re concentration

$C_x$ : Rectified indicates the correction factor for evaluated metals

In addition, quality controls ( $\text{HNO}_3$  0.37N, STD-2B in dilutions 100, 50, 25 and 5 %, EPOND-1 and SLRS-5) were used every eight samples, to calculate the background noise of the equipment and determine the loss of sensitivity over time. In all cases, this was corrected based on the correction of the internal standard.

### Determination of microbiological parameters

The determinations were made in the UNAH microbiology laboratories. The microorganism count was made from the water samples taken at the Aljibe (G2), ICA (M5) and Violento (M3) monitoring stations, the first two due to receiving a significant organic pollutant load (dairy derivatives and animal waste) and the last because it is located between them, as a way of controlling the purification process of the river itself.

For the isolation of total microorganisms, the technique of quantitative dilutions and sowing in a Petri dish (17) were used, with a dilution order of up to 109 for bacteria. The isolation was carried out in Nutrient Agar culture medium with incubation for 72 h. Morphophysiological identification was carried out according to the technique described by Bergey (18). For the counting of fecal coliform microorganisms, the method of the most probable number MPN (19) and the Cuban standard that determines the microbiological water quality was used (20).

## Statistical analysis

The spatio-temporal differences in the composition of pH, EC, majority elements and organic composition were determined from a multivariate variance analysis of double classification (bifactorial ANOVA), with the objective of knowing if there was variability due to the interaction of both factors (Sampling stations and Sampling time) or only by their main effects (factors separately). The parameters with significant differences were subsequently performed Duncan's test ( $p < 0.05$ ).

The content of heavy metals and fecal coliforms was compared with the Cuban standard for drinking water (8) and with the WHO standard for irrigation water (4).

## RESULTS AND DISCUSSION

The bifactorial analysis of variance to determine the spatio-temporal differences in the composition of t Mampostón sub-basin surface water showed that, in the case of the

interaction between the proposed factors (sampling stations and sampling time), there are no differences statistically significant in none of the parameters analyzed (Table 2), so the main effects were assessed separately.

### Spatial differences in the physical-chemical composition of Mampostón sub-basin surface waters

#### pH and EC

The pH of Mampostón sub-basin surface waters showed little spatial variability (Table 3), which is in line with the powerful buffering effect produced by the  $\text{HCO}_3^-$  and  $\text{Ca}^{2+}$  ions when dissolved (21). The general mean was 7.26, but without significant differences between the monitoring stations for  $p > 0.05$ .

EC determinations were higher than  $318 \mu\text{S cm}^{-3}$ , which indicated that there are no water permeability problems in the soil according to what was previously indicated (22).

**Table 2.** Multivariate analysis of double classification for the case of the evaluated factor interaction.

Factors	Parameters	Sum of squares type II	Quadratic mean	F	p	
Interaction effects between sampling stations and sampling time	pH	2,10	0,14	0,303	0,992 ns	
	CE	359871,93	23991,46	0,648	0,813 ns	
	Organic matter	COD	232,29	15,48	0,847	0,623 ns
		COP	25367,33	1691,15	0,662	0,800 ns
		NOP	465,79	31,05	1,069	0,420 ns
		DQO	116823,25	7788,21	0,586	0,864 ns
		$\text{DBO}_5$	142312,85	9487,52	1,845	0,072 ns
	Majority anions	$\text{HCO}_3^-$	37123,23	2141,54	1,010	0,761 ns
		$\text{SO}_4^{2-}$	613,93	40,92	0,599	0,853 ns
		$\text{Cl}^-$	3160,00	210,66	1,719	0,097 ns
		$\text{NO}_3^-$	27,10	1,80	0,783	0,686 ns
	Majority cations	$\text{Na}^+$	277,37	18,49	0,538	0,898 ns
		$\text{K}^+$	275,94	18,39	1,271	0,275 ns
		$\text{Mg}^{2+}$	66,61	4,44	0,652	0,809 ns
		$\text{Ca}^{2+}$	5190,22	346,01	0,916	0,556 ns
		Heavy methals	Cr total	1497,88	99,85	0,872
	$\text{Cu}^{2+}$		1191,08	79,40	0,897	0,574 ns
	$\text{Zn}^{2+}$		466301,98	31086,79	0,950	0,524 ns
	As total		0,96	0,06	0,702	0,763 ns
	$\text{Pb}^{2+}$		51003,2	3400,21	0,923	0,550 ns


Fisher's F-F; p-probability; ns-there are no statistically significant differences

**Table 3.** Determination of spatial differences for pH and EC parameters.

Parameters	Hydrosystem	N	$\bar{x}$	SD ( $\bar{x}$ )	F	p
pH	Ganuja river	16	6.79	0.53	1.15	0.33 ns
	Mampostón river	16	6.81	0.44		
	Pedroso diverter dam	16	7.29	0.82		
	Mampostón Dam	16	7.38	0.64		
EC	Ganuja river	16	696.18 a	272.9	9.60	0.000*
	Mampostón river	16	496.40 b	89.68		
	Pedroso diverter dam	16	441.30 b	60.02		
	Mampostón Dam	26	330.61 c	20.04		

N- number of samples;  $\bar{x}$ - arithmetic mean; SD ( $\bar{x}$ ) - Standard deviation of the mean; Fisher's F-F; p- probability; ns- there are no statistically significant differences; different letters in the same column indicate significant differences according to Duncan for  $p < 0.05$

Spatially, there are statistically significant differences in the EC of the different hydrosystems evaluated (rivers and dams), the Ganuza river having a higher concentration of dissolved salts and Mampostón dam having a lower concentration. However, when breaking down the different sampling stations in the bar graph (Figure 2), it can be clearly observed how these differences are related to the anthropic contribution at stations G2 and G3 on Ganuza river and M5 on Mampostón river.



The boxes represent the values of 25-75 % of the sample  
The mean is represented as a horizontal black line. The vertical bars represent the standard error of the mean (N = 64)

**Figure 2.** Electrical conductivity of the dissolved phase.

The use of water from these three sampling stations for irrigation implies a risk of soil salinization, since the observed values are higher than the FAO standard (23). The EC is influenced, both by the specific electrical conductivity (ECi) of the ions dissolved in water, and by the contributions of organic matter (OM) from the medium that can dissociate (as weak acids), releasing hydronium ions with high ECi. In this regard, it was reported that, the greater amount of both exists, the higher the EC of a water in a given site (21,24).

### Majority elements (anions and cations)

$\text{Ca}^{2+}$  was the predominant cation (Table 4), which apparently its contribution is anthropic, in organic form (G2), from the soy yogurt production process, which can induce the precipitation of toxic metals (24). The rest of the spatial differences that were found are caused by different local geopedological processes (25) and coincide with reports made in this same area in the previous decade (26). The  $\text{Na}^+$  and  $\text{K}^+$  cations presented higher concentrations in stations G1, G2 and G3, indicating anthropic contributions as part of the dumping of waste from the dairy and rum factories. The production processes carried out in these companies introduce high concentrations of salts, mainly  $\text{NaCl}$ ,  $\text{NaHCO}_3$ ,  $\text{Mg}(\text{NO}_3)_2$  and  $\text{KNO}_3$ .

The surface water that flows through the Ganuza and Mampostón rivers, as well as the one that is impounded in Pedroso diverter dam and the Mampostón dam presented high contents of dissolved  $\text{HCO}_3^-$ , in a variable composition, spatially according to the geology of the area (Table 5), which coincides with the results obtained previously (26).

The spatial differences in the concentrations of  $\text{Cl}^-$  and  $\text{NO}_3^-$  are related to the aforementioned productive processes (companies whose discharge is carried out in the waters of the Ganuza tributary), including the discharge of waste from the Institute of Animal Science (M5) for the first anion.

The classification of the surface waters that circulate through the basin are considered as bicarbonate, sodium calcium sulfate ( $\text{HCO}_3^- > \text{Ca}^{2+} = \text{SO}_4^{2-} > \text{Na}^+$ ), corresponding to the lithological constitution of the area. In this regard, other authors point out that the dissolution of calcite produces waters with a Ca/Mg ratio between 4-50  $\text{mmol L}^{-1}$  (26), being in the present study between 8.38-21.55  $\text{mmol L}^{-1}$ .

### Organic composition of the dissolved and particulate phases transported in suspension

The evaluation of the dissolved organic carbon (DOC) content showed that there were statistically significant spatial differences between the G3 monitoring station and the rest. The stations with the highest concentration of particular organic carbon (POC) were G2 and G3, the rest have lower POC values. Therefore, it was considered that a wide variability was observed in the carbon determinations (Table 4).

The relationship between C and N that is transported in suspended matter was shown through the C/N relationship. C/N values between 2.6 and 8.0 indicated a predominance of autochthonous organic matter, either due to photosynthesis or bacterial chemosynthesis or due to the presence of fluvial phytoplankton (27,28). Following the aforementioned criteria, the monitoring stations where autochthonous organic matter predominates are G2 and G3. This could be because the residues from the yogurt and rum factory are easily degradable and cause intense microbial growth on the water surface, visible to the naked eye by flocculation film formation (29).

On the other hand, C/N values between 8.1 and 12.0 indicated an allochthonous character, originating from contamination by waste from livestock companies that dump directly into the Mampostón sub-basin, for which values higher than 12.1 are considered to be comes from fertilized soils (25). The sampling stations with organic matter of animal origin are G1, G4, M1, M3, M4, M5, P1, P3 and P4. The sampling stations presented an edaphic origin of organic matter: M2, P2, PM1, PM2 and PM3 (Table 6).

### BOD<sub>5</sub> and COD

From the spatial point of view, the station with the highest BOD<sub>5</sub> and COD was M5, followed by G3 (Table 6). The rest of the stations do not present significant differences for both parameters. According to the American Public Health Society (30), drinking water has a BOD<sub>5</sub> of 0.75-1.5  $\text{mg L}^{-1}$  of oxygen and the water is considered contaminated if the BOD<sub>5</sub> is greater than 5.0  $\text{mg L}^{-1}$ , industrial and agricultural wastes contain levels of BOD<sub>5</sub> and COD above one hundred.

**Table 4.** Spatial variation of the majority cations and heavy metals in Mampostón sub-basin surface waters.

Cations (statistics)		Ganuja river				Mampostón river					Pedroso diverter dam				Mampostón dam			F	p
		G1	G2	G3	G4	M1	M2	M3	M4	M5	P1	P2	P3	P4	PM1	PM2	PM3		
<b>Majority elements</b>		(mg L <sup>-1</sup> )																	
Ca <sup>2+</sup>	$\bar{x}$	60,9bc	119,3a	78,3b	43,8cd	47,7cd	41,3cd	39,0d	71,9bc	57,9bc	73,2bc	64,8bc	57,9bc	52,2bc	38,8d	38,0d	38,8d	4,5	0,000*
	SD ( $\bar{x}$ )	16,7	32,4	31,1	6,7	19,7	10,6	21,2	29,2	25,9	15,8	23,3	7,6	19,0	8,7	9,4	9,2		
Mg <sup>2+</sup>	$\bar{x}$	4,2	5,6	7,2	4,2	4,2	4,4	4,1	5,4	3,9	5,9	5,8	5,8	6,2	4,6	4,6	4,7	0,6	0,8 ns
	SD ( $\bar{x}$ )	1,0	1,3	0,8	0,5	0,8	0,7	1,2	3,3	0,4	4,6	3,9	4,1	4,6	0,4	0,5	0,8		
Na <sup>+</sup>	$\bar{x}$	10,7b	63,3a	59,7a	11,4b	13,1b	13,6b	12,9b	15,7b	10,8b	13,0b	12,9b	12,3b	11,7,b	14,6b	14,8b	15,2b	37,9	0,000*
	SD ( $\bar{x}$ )	5,6	10,7	4,8	7,0	2,3	2,8	4,2	10,4	2,6	4,4	3,3	2,3	3,6	2,9	3,8	4,5		
K <sup>+</sup>	$\bar{x}$	5,8bc	9,9b	22,0a	4,4bc	4,1bc	4,6bc	4,5bc	5,3bc	4,9bc	2,7c	3,2bc	2,3c	2,3c	4,6bc	4,4bc	4,4bc	5,5	0,000*
	SD ( $\bar{x}$ )	3,6	3,8	14,3	1,0	1,5	0,9	0,5	3,3	1,9	0,9	0,8	0,5	0,6	0,6	0,4	0,5		
<b>Heavy metals</b>		(µg L <sup>-1</sup> )																	
Cr total	$\bar{x}$	7,4	23,6	19,3	8,4	9,3	6,3	8,0	13,4	8,0	7,1	10,0	8,0	7,0	16,2	8,9	4,9	0,4	0,9 ns
	SD ( $\bar{x}$ )	5,2	16,5	11,1	3,1	5,9	3,8	1,2	9,4	3,5	2,6	5,7	4,5	4,7	9,7	4,0	1,7		
Cu <sup>2+</sup>	$\bar{x}$	3,4	4,8	9,1	5,0	10,3	4,6	4,8	24,3	2,6	4,0	2,8	3,2	2,4	4,1	3,7	2,6	0,9	0,5 ns
	SD ( $\bar{x}$ )	2,5	2,2	5,7	1,4	5,2	2,7	2,7	19,7	1,7	1,4	1,4	2,3	1,6	2,5	1,2	1,5		
Zn <sup>2+</sup>	$\bar{x}$	25,8 b	78,8 b	277,4 a	32,2 b	329,7a	30,3 b	26,8 b	33,7 b	41,0 b	53,4 b	264,3 a	36,0 b	23,3 b	40,4 b	33,5 b	36,1 b	30,9	0,000*
	SD ( $\bar{x}$ )	13,9	36,1	143,4	12,7	173,7	18,5	16,1	17,3	22,7	22,4	138,2	22,0	11,7	12,2	7,1	15,4		
As total	$\bar{x}$	0,7	0,4	0,7	0,5	0,5	0,7	0,5	0,9	0,5	0,5	0,5	0,4	0,5	0,7	0,7	0,7	1,0	0,4 ns
	SD ( $\bar{x}$ )	0,2	0,2	0,1	0,3	0,2	0,1	0,1	0,4	0,1	0,2	0,1	0,1	0,2	0,2	0,1	0,1		
Pb <sup>2+</sup>	$\bar{x}$	27,2 b	97,2 a	12,8 c	38,6 b	4,6 c	20,5 b	87,9 a	5,4 c	3,6 c	85,5 a	10,0 c	6,8 c	2,0 c	2,8 c	2,4 c	2,4 c	35,4	0,000*
	SD ( $\bar{x}$ )	15,3	64,4	8,4	20,1	3,8	10,9	32,9	2,5	1,9	33,2	1,1	4,0	0,6	1,1	0,9	0,5		

$\bar{x}$ - arithmetic mean; SD ( $\bar{x}$ ) - Standard deviation of the mean; Fisher's F-F; p- probability; ns- non-significant differences for the same row and different letters in the same row- statistically significant differences according to Duncan for p <0.05

On the other hand, the BOD<sub>5</sub>/COD ratio indicated that organic matter is easily biodegradable in stations G2, G3, M4 and M5 with values equal to or greater than 0.5 (15). Aspect that is closely related to the type of waste dumped at these points.

### Heavy metals

The reported values of heavy metals for the international standard SLRS-5 satisfied the specifications of the specialized literature (20). All this for the satisfactory work, certification of processing the samples and the equipment operation, since all the values measured in the reference material ranged between 8 and 120 % of the coating factor, with respect to the certified values (Table 7). This indicated that the values reported for the sub-basin samples are reliable.

Among the heavy metals evaluated, only Zn<sup>2+</sup> and Pb<sup>2+</sup> showed statistical differences in their spatial distribution.

Zn<sup>2+</sup> presented its highest concentration in stations G3, M1 and P2 (Table 5). However, in none of the cases does

it exceed the Cuban Standard for drinking water (8) and the WHO Standard for irrigation water (4), which set the maximum value of this element at 5,000 µg L<sup>-1</sup> for safe exploitation. The concentrations reported do not constitute a limitation for its use.

Regarding the average content of Pb, there is widespread contamination by this element in the surface waters of the Ganuja and Mampostón tributaries and Pedroso diverter dam. The sampling stations with the highest concentrations are G2, M3 and P1, with statistical differences compared to the rest of stations. A second group with average content of Pb in solution is constituted by stations G1, G4 and M2. In all cases, presumably, because the low flow of both tributaries produces a retreat of the water in some points and, therefore, the organic matter and cations contributed by the discharges of the industries remain stagnant, accumulating in the sediments until the beginning of the rainy season (31). These six sampling stations exceed the permissible levels established for drinking water by Cuban regulations (8) and the WHO regulations for irrigation water (4) set at 10 µg L<sup>-1</sup>.

**Table 5.** Spatial variation of the majority anions in Mampostón sub-basin surface waters.

Majority anions (statistics)	Ganuja river			Mampostón river					Pedroso diverter dam				Mampostón dam			F	p		
	G1	G2	G3	G4	M1	M2	M3	M4	M5	P1	P2	P3	P4	PM1	PM2			PM3	
HCO <sub>3</sub> <sup>-</sup>	x	343,5b	364,0 b	305,7 b	280,7bc	199,7cd	186,7 cd	288,7bc	351,0b	523,2 a	262,0 bc	275,2 bc	232,5 bc	289,7 bc	135,0 d	133,2 d	140,0 d	14,0	0,000*
	SD (x̄)	67,3	140,1	9,9	23,7	25,2	61,7	65,1	16,4	42,3	43,1	61,9	51,0	49,2	12,9	14,1	12,1		
Cl <sup>-</sup>	x	25,7b	54,7a	21,5c	23,7c	22,2c	17,7cd	22,7c	22,7c	44,0a	23,2c	18,7cd	20,0c	26,0b	14,2cd	14,7cd	15,2cd	3,0	0,02 ns
	SD (x̄)	2,7	14,5	2,3	3,8	3,1	4,1	3,28	2,6	14,1	3,7	2,5	4,0	2,9	0,9	0,5	0,9		
NO <sub>3</sub> <sup>-</sup>	x	2,4b	2,4b	15,0a	1,4b	0,8b	1,1b	1,1b	4,1b	0,8b	2,0b	0,9b	1,9b	0,8b	0,8b	0,8b	0,8b	22,4	0,000*
	SD (x̄)	2,0	2,1	2,4	0,6	0,1	0,5	0,5	2,8	0,1	0,1	0,1	1,5	0,1	0,1	0,2	0,1		
SO <sub>4</sub> <sup>2-</sup>	x	20,5	20,7	16,7	20,7	20,7	13,5	22,2	16,2	41,0	16,2	16,5	19,2	20,0	20,2	20,0	20,2	2,1	0,2ns
	SD (x̄)	1,7	7,4	2,8	9,5	7,1	2,3	6,2	3,2	22,4	4,6	5,9	13,3	6,8	0,9	0,8	1,2		

x̄ - mean; SD (x̄) - Standard deviation of the mean; Fisher's F-F; p - probability, ns - non-significant differences and different letters in the same row - statistically significant differences according to Duncan for p < 0,05)

**Table 6.** Spatial variation of the organic composition of Mampostón sub-basin surface waters.

Parameters	Ganuja river			Mampostón river					Pedroso diverter dam				Mampostón dam			F	p		
	G1	G2	G3	G4	M1	M2	M3	M4	M5	P1	P2	P3	P4	PM1	PM2			PM3	
DOC	x	8,3bc	7,4bc	17,1a	6,7bc	12,3b	7,5c	8,1bc	5,2c	5,0c	4,6c	6,7bc	6,0bc	8,7bc	9,3bc	6,7bc	2,9	0,020 ns	
	SD (x̄)	3,8	4,4	2,9	2,3	3,3	3,6	3,3	1,8	1,3	1,9	4,4	2,6	2,8	3,4	2,5			
POC	x	24,2c	172,1a	107,4a	8,1c	13,7c	9,8c	10,1c	22,0c	67,7b	76,1b	30,0bc	29,3bc	28,5bc	32,0bc	52,5b	43,7bc	3,9	0,001*
	SD (x̄)	20,4	74,5	69,6	5,8	14,2	8,6	8,2	17,8	63,7	67,7	25,0	25,3	18,0	24,1	43,0	37,7		
NOP	x	2,7c	21,5a	13,7b	0,8c	1,0c	0,7c	0,9c	7,0c	7,8c	2,2c	2,6c	2,5c	2,9c	2,9c	2,7c	4,2	0,000*	
	SD (x̄)	2,3	11,5	13,2	0,2	0,9	0,5	0,6	1,3	6,7	5,7	1,4	2,3	1,7	2,1	3,6	2,3		
Ratio C/N	x	8,9	8,0	7,2	10,1	13,7	14	11,2	9,6	9,7	13,6	11,2	11,4	12,0	13,4	16,1	-	-	
	SD (x̄)	17,0c	27,2c	178,5b	4,7c	3,9c	1,8c	7,4c	482,2a	1,8c	8,7c	8,5c	2,6c	1,8c	1,7c	1,9c	8,7	0,000*	
BOD <sub>5</sub>	x	11,8	25,1	92,1	2,0	2,2	0,9	7,1	6,4	298,1	0,4	6,3	6,5	1,0	0,6	0,8	0,4		
	SD (x̄)	39,2c	55,5c	355,7b	15,2c	14,5c	8,0c	17,2c	664,5a	8,0c	19,5c	30,0c	11,7c	8,4c	8,7c	8,5c	11,1	0,000*	
COD	x	11,0	17,1	281,7	9,3	10,4	1,2	11,6	9,3	317,8	1,8	10,3	26,4	4,7	2,4	1,9	2,0		
	SD (x̄)	0,4	0,5	0,5	0,3	0,2	0,2	0,4	0,6	0,7	0,4	0,3	0,2	0,2	0,2	0,2	0,2	-	-

x̄ - mean; SD (x̄) - Standard deviation of the mean; Fisher's F-F; p - probability; ns - non-significant differences for the same row and different letters in the same row - statistically significant differences according to Duncan for p < 0,05

**Table 7.** Validation of analytical work in the processing of samples for the determination of heavy metals.

Metal	Measured concentration	International Standard SLRS-5 Certified concentration ( $\mu\text{g L}^{-1}$ )	Coating Factor (%)
Cr	0.36 $\pm$ 0.1	0.31 $\pm$ 0.003	115
Cu	13.8 $\pm$ 0.1	17.4 $\pm$ 1.3	80
Zn	0.8	0.8 $\pm$ 0.1	99
As	0.46	0.41 $\pm$ 0.003	114
Pb	0.078	0.081 $\pm$ 0.006	97

Despite the use of unleaded fuels, since 2000 in Cuba, Pb is a metal with low mobility, which results in its accumulation in soils in high-traffic areas, due to contamination from previous decades (32). Therefore, the Pb content accumulated in the soils around the asphalt factory (station M2) and the national highway (station M3) may have been washed away by rain, wind or human activities, and deposited in these areas from the river. Another source of this element may be related to waste from the paint factory (G4), a point before station M2, and leaks of used oil from the boilers of the pasteurizer "El Aljibe", which contaminates stations G1 and G2.

The contamination of the water at station P1 (Pedroso diverter dam) could be due to the negligent dumping of urban solid waste and sewage water on its margins, an aspect notified to the pertinent authorities and subsequently corrected.

### Temporal differences in the physical-chemical composition of the Mampostón sub-basin surface waters

There is little seasonal variability in the physical-chemical parameters evaluated (Table 8). These results indicated the anthropic influence on the composition of surface waters in the territory, since the seasonal differences inherent to the concentration of elements in dry season are eliminated by the constant contributions received, from the waste from the companies. In addition, it was reported that this phenomenon might also be due to the bidirectional water exchange system between the Pedroso diverter dam and the Mampostón dam, which can occur both through the artificial channel and through the river (31). There are significant differences in pH, which increases 0.6 units in dry season, although its character continues to oscillate around neutrality.

The content of  $\text{SO}_4^{2-}$  dissolved in the water is higher in dry season (Table 8). The  $\text{SO}_4^{2-}$  concentrations found are not lithologically justified and it constitutes an anthropic contribution, in accordance with the information reported by other authors (21). The content of  $\text{SO}_4^{2-}$  and  $\text{Cl}^-$  in karst basins depends on the presence of gypsum (nonexistent in this sub-basin) or saline rocks, respectively, or on processes produced by human activity and that are related to agricultural fertilization, which are it increases in the months of October-February, according to reports from the Mayabeque Agriculture Delegation (33).

These results indicated the anthropic influence on the composition of surface waters in the territory, since the seasonal differences inherent to the concentration of elements in dry season are eliminated by the constant contributions received from the waste from the companies. In addition, it was reported that this phenomenon might also be due to the bidirectional water exchange system between Pedroso diverter dam and the Mampostón dam, which can occur both through the artificial channel and through the river (31).

### Content of total microorganisms and fecal coliforms

Regarding the total microbial count in water (Table 9), as well as the concentrations of fecal coliforms, they showed that the presence of fecal coliforms in the water of the Aljibe station (G2) does not exceed the permissible limits for water for agricultural use. The restriction of the water use of f this station for the irrigation is due to its content of  $\text{Na}^+$  and  $\text{Pb}^{2+}$  and not to the presence of fecal pathogens.

According to this indicator, the water in the section of Mampostón River, included in the sampling station M5, should not be used in the irrigation of root and leaf crops, as well as for long-stemmed crops, if the applied irrigation is drip nor in labor-intensive or highly mechanized agriculture (34). In the case of the Violento station (M3), results show that the water should not be used for irrigation, regardless of crop type.

The evaluation of the spatio-temporal differences of the chemical-physical parameters allowed to establish the influence of the various polluting sources of the territory, on the average composition of the surface waters with respect to a great diversity of parameters and also to verify the aptitude for irrigation in the sampling stations evaluated. This approach has been widely used in the evaluation of the anthropic contribution to soils and waters, both surface and underground (35-38).

This work has made it possible to establish a work tool for the design of an adequate management plan, with a view to reversing the impacts of organic and inorganic pollution by the Territorial Council of Hydrographic Basins. It is important taking into account that the implementation of a coordinated work between decision-makers and environmental managers, it guarantees to put into practice ecological compensation strategies and the optimization of the industrial structure, as bases for obtaining a sustainable ecosystem (39).

**Table 8.** Determination of the temporal differences of the evaluated parameters.

Parameter		Season	$\bar{x}$	SD ( $\bar{x}$ )	F	p
pH		Little Rainy	7,4 a	0,5	8,20	0,006*
EC		Rainy	6,8 b	0,5		
(μS cm <sup>-3</sup> )		Little Rainy	477,2	289,8	0,37	0,542 ns
Majority Anions	HCO <sub>3</sub> <sup>-</sup>	Rainy	526,0	345,0		
	(mg L <sup>-1</sup> )	Little Rainy	279,9	122,2	0,581	0,449 ns
	SO <sub>4</sub> <sup>2-</sup>	Rainy	258,9	96,3		
	(mg L <sup>-1</sup> )	Little Rainy	22,6 a	11,0	4,394	0,04*
	Cl <sup>-</sup>	Rainy	17,9 b	6,1		
	(mg L <sup>-1</sup> )	Little Rainy	25,7	18,4	0,642	0,426 ns
Majority cations	NO <sub>3</sub> <sup>-</sup>	Rainy	22,7	10,3		
	(mg L <sup>-1</sup> )	Little Rainy	4,0	2,4	0,172	0,68 ns
	Na <sup>+</sup>	Rainy	3,2	2,0		
	(mg L <sup>-1</sup> )	Little Rainy	18,6	16,9	0,066	0,798 ns
	K <sup>+</sup>	Rainy	19,6	17,0		
	(mg L <sup>-1</sup> )	Little Rainy	7,3	6,3	0,906	0,345 ns
Organic matter	Mg <sup>2+</sup>	Rainy	4,9	3,6		
	(mg L <sup>-1</sup> )	Little Rainy	5,3	3,0	0,706	0,404 ns
	Ca <sup>2+</sup>	Rainy	4,8	1,3		
	(mg L <sup>-1</sup> )	Little Rainy	52,7	23,2	2,295	0,135 ns
COD		Rainy	62,8	29,8		
	(mg L <sup>-1</sup> )	Little Rainy	9,0	5,1	3,77	0,05 ns
COP		Rainy	6,7	4,0		
	(mg L <sup>-1</sup> )	Little Rainy	53,4	35,6	1,10	0,29 ns
NOP		Rainy	64,4	51,2		
	(mg L <sup>-1</sup> )	Little Rainy	6,5	3,8	0,99	0,32 ns
DBO <sub>5</sub>		Rainy	7,8	5,3		
	(mg L <sup>-1</sup> )	Little Rainy	179,0	60,0	0,10	0,74 ns
DQO		Rainy	79,0	29,0		
	(mg L <sup>-1</sup> )	Little Rainy	223,7	39,5	0,79	0,37 ns
Heavy metals	Cr total	Rainy	169,0	79,6		
	(mg L <sup>-1</sup> )	Little Rainy	9,5	4,1	0,70	0,40 ns
Cu <sup>2+</sup>		Rainy	9,9	2,1		
	(mg L <sup>-1</sup> )	Little Rainy	4,3	2,4	0,98	0,32 ns
Zn <sup>2+</sup>		Rainy	6,6	3,1		
	(mg L <sup>-1</sup> )	Little Rainy	97,0	54,3	0,71	0,40 ns
As total		Rainy	91,9	35,1		
	(mg L <sup>-1</sup> )	Little Rainy	0,6	0,2	0,31	0,57 ns
Pb <sup>2+</sup>		Rainy	0,6	0,3		
	(mg L <sup>-1</sup> )	Little Rainy	28,1	9,2	0,06	0,79 ns
		Rainy	31,9	7,5		

$\bar{x}$ - mean; SD ( $\bar{x}$ ) - Standard deviation of the mean; Fisher's F-F; p- probability; ns- non-significant differences; Different letters in the same column for each parameter indicate statistically significant differences according to Duncan for p <0.05

**Table 9.** Count of total microorganisms and fecal coliforms in three sampling stations of the Mampostón sub-basin.

Monitoring station	Total microorganism (CFU mL <sup>-1</sup> )	Morphoty pes	Fecal coliforms (UFC mL <sup>-1</sup> )
G2	13x10 <sup>3</sup>	6	11x10 <sup>3</sup>
M3	2x10 <sup>5</sup>	8	2x10 <sup>5</sup>
M5	2.8x10 <sup>5</sup>	7	2x10 <sup>6</sup>

CFU-Colony Forming Units

## CONCLUSIONS

- The spatial variability is the determining factor to explain the variance of the different parameters evaluated relative to the quality of the waters in the Mampostón sub-basin. Its analysis allows determining the aptitude for irrigation of 16 sampling stations, based on the knowledge of the main pollutants and their sources of discharge.
- The sampling stations G2, G3 (Ganuzá river) and M5 (Mampostón river), present organic and soluble salts contributions that establish limitations for their use in agricultural irrigation. While the average concentrations of dissolved Pb, disable the operation of stations G1, G2, G4 (Ganuzá river), M2 and M3 (Mampostón river) and P1 (Pedroso diverter dam). The M5 station also has concentrations dangerous to human health of fecal coliforms.
- The rest of the stations located in the Pedroso diverter dam and the Mampostón dam, comply with all the quality standards for agricultural irrigation.
- A monitoring and management program for the area must be designed, which makes it possible to assess the risk of exposure to pollutants and the implementation of an action plan that allows its mitigation.

## BIBLIOGRAPHY

1. Wilcox Lv. Classification and use of irrigation waters. Circular No.969, Washington, D.C: US Department of Agriculture; 1955. 19 p.
2. Chang F-J, Tsai Y-H, Chen P-A, Coyne A, Vachaud G. Modeling water quality in an urban river using hydrological factors-Data driven approaches. 2015;151.
3. Wu X, Cobbina SJ, Mao G, Xu H, Zhang Z, Yang L. A review of toxicity and mechanisms of individual and mixtures of heavy metals in the environment. *Environmental Science and Pollution Research*. 2016;23(9):8244-59.
4. Chang A, Pan G, Asano T, Schonning T. WHO guidelines for the safe use of wastewater excreta and greywater. *Wastewater Use in Agriculture*. Vol. 2. World Health Organization; 2006. 397 p.
5. García-Fernández JM, Gutiérrez-Díaz JB. Un índice para evaluar la calidad de los recursos hídricos superficiales en cuencas hidrográficas (ICAsp 2014). *Voluntad Hidráulica*. 2015;113.
6. Quiroz Fernández LS, Izquierdo Kulich E, Menéndez Gutiérrez C. Aplicación del índice de calidad de agua en el río Portoviejo, Ecuador. *Ingeniería Hidráulica y Ambiental*. 2017;38(3):41-51.
7. Rodríguez-Miranda JP, Serna-Mosquera JA, Sánchez-Céspedes JM. Índices de calidad en cuerpos de agua superficiales en la planificación de los recursos hídricos. *Revista Logos, Ciencia & Tecnología*. 2016;8(1):159-67.
8. Oficina Nacional de Normalización. Norma Cubana Obligatoria NC 827. Agua potable. Requisitos sanitarios. La Habana: ONN; 827, 2017. p. 1-13.
9. Oficina Nacional de Normalización. Norma Cubana Obligatoria NC 27. Vertimiento de Aguas Residuales a las aguas terrestres y al Alcantarillado. Especificaciones. La Habana: ONN; 27, 2012. p. 1- 14.
10. Oficina Nacional de Estadística e Información. Anuario Estadístico de Cuba. La Habana: ONEI. 2020;447.
11. Barranco-Rodríguez G. La problemática ambiental y la ordenación de la cuenca hidrográfica Mayabeque, Cuba. *Mapping*. 2005;(101):44-51.
12. Casanueva-Marengo MJ, Díaz-de Alba MI, Granado-Castro MD, Galindo-Riaño MD. Metales en ecosistemas acuáticos. *Métodos de análisis y especiación química analítica de metales en aguas*. Editorial Académica Española; 2018 . 292 p. Available from: <https://www.morebooks.de/store/es/book/metales-en-ecosistemas-acu%C3%A1ticos-m%C3%A9todos-de-an%C3%A1lisis-y-especiaci%C3%B3n/isbn/978-620-2-13914-4>
13. Aguinaga S. Manual de procedimientos analíticos para aguas y efluentes . Dirección Nacional de Medio Ambiente; 1996 . 174 p. Available from: <https://www.yumpu.com/es/document/read/14893851/manual-de-procedimientos-analiticos-para-aguas-y-efluentes>
14. N'guessan YM, Probst J-L, Bur T, Probst A. Trace elements in stream bed sediments from agricultural catchments (Gascogne region, SW France): where do they come from? *Science of the total environment*. 2009;407(8):2939-52.
15. Aznar-Jimenez A. Determinación de los parámetros físico-químicos de calidad de las aguas. *Revista Manuel de gestión ambiental*. 2000;2(23):12-9.
16. NRC-CNRC (National Research Council of Canada. Ottawa. Canada). River water reference material for trace metals . 2009 . Available from: <http://www.speciation.net/Database/Materials/National-Research-Council-of-Canada-NRC--CNRC/SLRS5-River-water-reference-material-for-trace-metals-;j1230>
17. Oblitas Terrones YG. Identificación de coliformes totales, coliformes fecales y *Escherichia coli* aisladas del agua potable del distrito de Cajamarca. . : Universidad Privada Antonio Guillermo Urrel; 2016 . 124 p. Available from: <http://repositorio.upagu.edu.pe/handle/UPAGU/454>
18. Bergey DH. Bergey's Manual of determinative bacteriology. Board and trustees. 7<sup>th</sup> Ed. Baltimore; 2010. 1268 p. Available from: <https://www.biodiversitylibrary.org/item/41848>
19. Quevauviller P, Maier EA. Quality assurance and quality control for environmental monitoring. In: *Quality assurance in environmental monitoring—sampling and sample pretreatment*. VCH Weinheim New York; 1995. p. 1-25.
20. Oficina Nacional de Normalización. Microbiología del agua. Detección y enumeración de coliformes. Técnica del número más probable (NMP) . La Habana; 1095, 2015 . Available from: <https://especialidades.sld.cu/higiene-epidemiologia/?s=NC+1095>
21. Álvarez A, Gutiérrez JE, Facundo JR, González R. Análisis hidrogeoquímico de las aguas de la subcuenca Mampostón. *Ciencias de la Tierra y el Espacio*. 2010;11:1-9.

22. Hernández-Baranda Y, Rodríguez-Hernández P, Peña-Icart M, González-Hernández P, Nicolás- López S, Tomás F. Caracterización química y agronómica de las aguas residuales del yacimiento Castellano, Pinar del Río. *Cultivos Tropicales*. 2018;39(3):11-7.
23. Ayers RS, Westcot DW. Water quality for agriculture. Food and Agriculture Organization of the United Nations Rome; 1985. 97 p.
24. Cartone A, Casolani N, Liberatore L, Postiglione P. Spatial analysis of grey water in Italian cereal crops production. *Land Use Policy*. 2017;68:97-106.
25. Paneque J, Fuentes E, Mesa A, Echemendía A. El mapa nacional de suelos escala 1: 25 000. In: *Memorias del XI Congreso Latinoamericano y II Congreso Cubano de la Ciencia del Suelo*, La Habana, Memorias,(DR Villegas y D. Ponce de León, eds.). 1991. p. 1345-7.
26. Fagundo-Castillo JR, González P. Hidrogeoquímica . España: Academia Española; 2012 . 364 p. Available from: <https://www.libreriauniversitaria.it/hidrogeoquimica-fagundo-castillo-juan-reynerio/book/9783847356127>
27. Bardhan P, Karapurkar SG, Shenoy DM, Kurian S, Sarkar A, Maya MV, et al. Carbon and nitrogen isotopic composition of suspended particulate organic matter in Zuari Estuary, west coast of India. *Journal of Marine Systems*. 2015;141:90-7.
28. Kendall C, Silva SR, Kelly VJ. Carbon and nitrogen isotopic compositions of particulate organic matter in four large river systems across the United States. *Hydrological Processes*. 2001;15(7):1301-46. <https://doi.org/10.1002/hyp.216>
29. Mayea S, Carone M, Novo R, Boado I, Silveira E. *Microbiología Agropecuaria*. Tomo II. Félix Varela; 2009. 281 p.
30. APHA-AWWA-WPCF. Métodos normalizados para el análisis de aguas potables y residuales . 17.ª ed. American Public Health Association Enc. New York.: Editorial Díaz de Santos, S.A.; 1992 . Available from: <https://dialnet.unirioja.es/servlet/libro?codigo=307542>
31. Mesa-Pérez MA, Díaz-Rizo O, García-Acosta H, Alarcón-Santos OA, Sánchez-Pérez JM. Relationship between micro-granulometric profile and chemical sediment composition in Mampostón sub-watershed, Mayabeque, Cuba. *Journal of South American Earth Sciences*. 2020;101:102538.
32. Guo G, Wu F, Xie F, Zhang R. Spatial distribution and pollution assessment of heavy metals in urban soils from southwest China. *Journal of Environmental Sciences*. 2012;24(3):410-8.
33. Ministerio de la Agricultura de Cuba. Informe anual sobre los resultados agrícolas de la provincia Mayabeque. Mayabeque: Ministerio de la Agricultura. 2014; p. 34.
34. Ríos-Tobón S, Agudelo-Cadavid RM, Gutiérrez-Builes LA. Patógenos e indicadores microbiológicos de calidad del agua para consumo humano. *Revista Facultad Nacional de Salud Pública*. 2017;35(2):236-47.
35. Scheili A, Rodriguez MJ, Sadiq R. Seasonal and spatial variations of source and drinking water quality in small municipal systems of two Canadian regions. *Science of the Total Environment*. 2015;508:514-24.
36. Cabrera Alfonso JR, Ponce de León Lima D, Cervantes Beyra R, Vargas Rodríguez H, Domínguez Palacio D. Distribución espacial de la calidad de las aguas subterráneas utilizadas para el riego. *Revista Ciencias Técnicas Agropecuarias*. 2015;24(3):13-21.
37. Zhou X, Lei K, Khu S-T, Meng W. Spatial flow analysis of water pollution in eco-natural systems. *Ecological Indicators*. 2016;69:310-7.
38. Zhao J, Lin L, Yang K, Liu Q, Qian G. Influences of land use on water quality in a reticular river network area: A case study in Shanghai, China. *Landscape and Urban Planning*. 2015;137:20-9.
39. Liu Y, Braits VF, Engel BA. Evaluating the effectiveness of management practices on hydrology and water quality at watershed scale with a rainfall-runoff model. *Science of the Total Environment*. 2015;511:298-308.